LRQ075HP-DE51T10A Datasheet

- 75, 150, 300, 450, 600 mm travel
- Up to 10 µm accuracy over 600 mm travel
- Up to 270 mm/s speed and up to 500 N thrust
- 100 kg load capacity
- Inline and parallel drive configurations
- Ball screw and lead screw configurations
- Integrated linear encoders with 50 nm resolution provide slip/stall detection and position correction
- Designed for use with an X-MCC Series stepper motor controller or any 2-phase stepper motor controller
- With AutoDetect, the X-MCC controller configures its settings automatically for the connected peripheral
- Custom versions available

LRQ-DE Series Overview

Zaber's LRQ-DE Series products are computer-controlled, motorized linear stages with high stiffness, load, and lifetime capabilities in a compact size. An integrated linear encoder combined with stage calibration provides high accuracy positioning over the full travel of the device. At only 36 mm high, these stages are excellent for applications where a low profile is required. These stages are capable of speeds up to 270 mm/s, and can bolt together into XY and XYZ systems. Some multi axis configurations may require additional accessories, please contact Zaber Technical Support to ensure the correct ones are selected. Each device is available in either an inline or parallel drive configuration.

The stages are designed to connect directly to our X-MCC Series universal motor controllers, or they can be used with any 2-phase stepper motor controller through the panel mount DB26 connector. Set up is easy with AutoDetect. Once connected, the X-MCC controller will automatically detect and configure the LRQ-DE.

For more information visit: https://www.zaber.com/products/linear-stages/LRQ-DE

LRQ-DE Series Part Numbering & Options



LRQ075HP-DE51T10A Drawings

- LRQxP-DET10A.png (Drawing for the LRQxP-DET10A)

LRQ075HP-DE51T10A Specifications

Microstep Size (Default Resolution)	**0.1953125 µm**
Built-in Controller	No
Recommended Controller	X-MCC (48 V) Recommended
AutoDetect	Yes
Travel Range	75 mm (2.953")
Accuracy (unidirectional)	13 µm (0.000512")
Repeatability	< 2 µm (< 0.000079")
Backlash	< 6.5 µm (< 0.000256")
Maximum Speed	110 mm/s (4.331"/s)
Minimum Speed	0.000119 mm/s (0.000005"/s)
Speed Resolution	0.000119 mm/s (0.000005"/s)
Encoder Type	Linear quadrature encoder
Encoder Resolution	50 nm
Peak Thrust	500 N (112.1 lb)
Back-driving Force*	(± 30%) 123 N (27.6 lb)
Maximum Continuous Thrust	200 N (44.9 lb)
Maximum Centered Load	1000 N (224.3 lb)
Maximum Moment (Pitch)	30 N-m (22.1 ft-lb)
Maximum Moment (Roll)	30 N-m (22.1 ft-lb)
Maximum Moment (Yaw)	30 N-m (22.1 ft-lb)
Vertical Runout	< 20 µm (< 0.000787")
Horizontal Runout	< 20 µm (< 0.000787")
Pitch	0.025° (0.436 mrad)
Roll	0.01° (0.174 mrad)
Yaw	0.02° (0.349 mrad)
Stiffness in Pitch	500 N-m/° (35 µrad/N-m)
Stiffness in Roll	1180 N-m/° (15 µrad/N-m)
Stiffness in Yaw	450 N-m/° (39 µrad/N-m)
Linear Motion Per Motor Rev	2.5 mm (0.098")
Motor Steps Per Rev	200
Motor Type	Stepper (2 phase)

Microstep Size (Default Resolution)	**0.1953125 µm**
Motor Rated Current	2300 mA/phase
Motor Winding Resistance	1 ohms/phase
Inductance	2.2 mH/phase
Motor Connection	D-sub 26
Default Resolution	1/64 of a step
Guide Type	Recirculating Ball Linear Guide
Mechanical Drive System	Precision ball screw
Limit or Home Sensing	Magnetic home sensor
Axes of Motion	1
Mounting Interface	M6 and M3 threaded holes
Operating Temperature Range	0 to 50 °C
CE Compliant	Yes
Vacuum Compatible	No
Weight	2.41 kg (5.313 lb)

LRQ-DE Series Charts



Thrust Speed Performance



Thrust Speed Performance




Thrust Speed Performance
LRQxxxAx-DE51T10A with X-MCCx 48V
LRQxxxBx-DE51T10A with X-MCCx 48V
LRQxxxHx-DE51T10A with X-MCCx 48V
Thrust (N)
Thrust (lb)
Speed (mm/s)
0
50
100
150
200
250
300
350
400
450
500
20
40
60
80
100

Typical Accuracy



LRQ Linear Bearing Lifetime



Contact

Email: contact@zaber.com
Phone (toll free Canada/USA): 1-888-276-8033
Phone (direct): 1-604-569-3780
Fax: 1-604-648-8033

Zaber Technologies Inc.
#2 - 605 West Kent Ave. N.
Vancouver, British Columbia
Canada, V6P 6T7
https://www.zaber.com