

GSM60-E03T4A Datasheet



- 40 mm and 60 mm centre of rotation options allow for two axes of motion about a common centre of rotation
- 30 N load capacity
- Low profile, small footprint
- Encoder position feedback with slip/stall detection and automatic recovery
- Designed for use with an X-MCC Series stepper motor controller or any 2-phase stepper motor controller
- With AutoDetect, the X-MCC controller configures its settings automatically for the connected peripheral


GSM-E Series Overview

Zaber's GSM-E Series devices are motorized goniometers with high thrust and speed capabilities in a compact package. They are stepper motor driven positioning goniometers designed to interface with our X-MCC controllers, offering high resolution daisy-chainable operation.

Set up is easy with AutoDetect. Once connected, the X-MCC controller will automatically detect and configure the GSM-E. These stages are excellent for applications where a small profile is required. They can mount to a flat surface or stack together to share a common centre of rotation for two axes of angular motion.

For more information visit: <https://www.zaber.com/products/goniometer-stages/GSM-E>

GSM-E Series Part Numbering & Options



GSM60-E03T4A Drawings

- [GSM-E.png \(Drawing for the GSM-E\)](#)

GSM60-E03T4A Specifications

Microstep Size (Default Resolution)	0.0001131413171° (1.975 µrad)
Built-in Controller	No
Recommended Controller	MCC (48 V) Recommended
AutoDetect	Yes
Range	+/-7°
Accuracy (unidirectional)	0.06° (1.047000 mrad)
Repeatability	< 0.005° (< 0.087 mrad)
Backlash	< 0.01° (< 0.174 mrad)
Maximum Speed	30°/s (5 rpm)
Minimum Speed	0.000069°/s (1.204 µrad/s)
Speed Resolution	0.000069°/s (1.204 µrad/s)
Encoder Resolution	200 CPR (800 states/rev)
Encoder Type	Rotary quadrature encoder
Maximum Centered Load	30 N (6.7 lb)
Rotation Centre Height	60 mm (2.362")
Rotation Centre Accuracy	< 0.1 mm (< 0.004")
Angular Motion Per Motor Rev	1.44820885888°
Motor Steps Per Rev	200
Motor Type	Stepper (2 phase)
Motor Rated Current	600 mA/phase
Motor Winding Resistance	6.5 ohms/phase
Inductance	3.5 mH/phase
Motor Connection	D-sub 15
Default Resolution	1/64 of a step
Motor Frame Size	NEMA 08
Guide Type	Crossed roller bearing
Mechanical Drive System	Precision Worm Gear
Limit or Home Sensing	Magnetic home and away sensors
Manual Control	Yes
Axes of Motion	1
Mounting Interface	M2 and M3 mounting holes

Microstep Size (Default Resolution)	0.0001131413171° (1.975 μrad)
Operating Temperature Range	0-50 °C
CE Compliant	Yes
Vacuum Compatible	No
Weight	0.24 kg (0.529 lb)

Contact

Email: contact@zaber.com

Phone (toll free Canada/USA): 1-888-276-8033

Phone (direct): 1-604-569-3780

Fax: 1-604-648-8033

Zaber Technologies Inc.

#2 - 605 West Kent Ave. N.

Vancouver, British Columbia

Canada, V6P 6T7

<https://www.zaber.com>