

X-DMA10A-AE55T17Q Datasheet



- 10mm travel
- High repeatability (50 nm), with 10 nm minimum incremental move
- Direct position measurement from 1 nm resolution linear encoder
- Non-contact direct-drive motor for high precision, high dynamic performance & reliability
- Built-in controller; daisy-chains with other Zaber products
- Digital IO, analog input, and optional encoder output for interfacing with external systems


X-DMA-AE Series Overview

Zaber's X-DMA-AE Series devices are computer-controlled, direct-drive linear stages delivering high speed, precision, and reliability in a compact size. A high resolution linear encoder results in repeatability less than 50 nm and consistent movement steps down to 10 nm. Low-friction high-rigidity crossed roller bearings allow for fast step and settle times and anti-creep bearing cages eliminate cage creep during vertical or high acceleration operation. Both the drive and encoder are non-contact, and have no moving cables, resulting in an extremely robust system.

X-DMA-AE are stand-alone units requiring only a standard 24 V or 48 V power supply. They connect to the RS-232 port or USB port of any computer, and can be daisy-chained with any other Zaber products. The daisy-chain also shares power, making it possible for multiple X-Series products to share a single power supply. Like all of Zaber's products, the X-DMA-AE Series is designed to be 'plug and play' and very easy to set up and operate. X-DMA-AE devices also include two digital inputs, a digital output, and an analog input for interfacing with external systems. An event-driven trigger system allows devices to be programmed for stand-alone operation based on I/O, time, or movement stimuli.

For more information visit: <https://www.zaber.com/products/linear-stages/X-DMA-AE>

X-DMA-AE Series Part Numbering & Options



X-DMA10A-AE55T17Q Drawings

- [X-DMA-AE.pdf \(Drawing for the X-DMA-AE\)](#)

X-DMA10A-AE55T17Q Specifications

Built-in Controller	
Travel Range	10 mm (0.394")
Accuracy (unidirectional)	8 μ m (0.000315")
Repeatability	< 0.05 μ m (< 0.000002")
Minimum Incremental Move	10 nm
Minimum Speed	0.61 nm/s
Speed Resolution	0.61 nm/s
Encoder Type	Linear analog encoder
Encoder Count Size	1 nm
Peak Thrust	15 N (3.4 lb)
Maximum Continuous Thrust	5 N (1.1 lb)
Communication Interface	RS-232
Communication Protocol	Zaber ASCII (Default)
Data Cable Connection	Locking 4-pin M8
Power Supply	48 VDC
Power Plug	2-pin screw terminal
Motor Type	Moving Magnet Voice Coil
Force Constant	2.23 N/A (0.5 lbs/A)
Guide Type	Anti-Creep Crossed-Roller Bearing
Limit or Home Sensing	Optical Index Mark
Manual Control	No
Axes of Motion	1
LED Indicators	Yes
Mounting Interface	M3 and M6 threaded holes
Moving Mass	0.18 kg (0.396 lbs)
Digital Input	2
Digital Output	1
Analog Input	1

Interpolated relative quadrature signal with differential

Built-in Controller	
Encoder Output Type	RS422 levels
Operating Temperature Range	0-50 °C
Vacuum Compatible	No
Typical Move and Settle Time (100 nm move, < 15 nm, 250 g load)	< 15 ms
Typical Move and Settle Time (250 nm move, < 15 nm, 250 g load)	< 15 ms
Weight	0.49 kg (1.080 lb)

Contact

Email: contact@zaber.com

Phone (toll free Canada/USA): 1-888-276-8033

Phone (direct): 1-604-569-3780

Fax: 1-604-648-8033

Zaber Technologies Inc.

#2 - 605 West Kent Ave. N.

Vancouver, British Columbia

Canada, V6P 6T7

<https://www.zaber.com>