

## X-NMS23-BE08P1 Datasheet



- NEMA 17 and 23 stepper motors with built-in controllers and encoders
- Up to 3000 rpm speed and 1.8 N-m torque
- Daisy-chains data and power with X-series products
- Home sensor and magnet included, optional away sensor
- Optional integrated power-off brake
- Custom versions available


## X-NMS-E Series Overview

These NEMA size 17 and 23 stepper motors have built-in controllers and encoders for stall detection and recovery. A detachable home sensor HS02 and magnet are included. An additional HS02L150 Hall effect sensor can be purchased to function as an away sensor. These motors are standalone units requiring only a standard 24 V or 48 V power supply.

An indexed knob provides convenient manual control for versatile operation even without a computer. The motors connect to the USB 2.0 or RS-232 port of any computer and can be daisy-chained with any other Zaber products. Convenient locking, 4-pin, M8 connectors on the unit allow for secure connection between units. An optional power-off brake is available on NEMA 23 sized steppers to secure the payload across power cycles. The chain also shares power, so multiple X-Series products can use a single power supply.

For more information visit: <https://www.zaber.com/products/stepper-motors/X-NMS-E>

## X-NMS-E Series Part Numbering & Options



## X-NMS23-BE08P1 Drawings


- [X-NMS23-BE.png \(Drawing for the X-NMS23-BE\)](#)

## X-NMS23-BE08P1 Specifications


<b>Microstep Size (Default Resolution)</b>	<b>0.028125° (490.866 μrad)</b>
Built-in Controller	Yes
Accuracy (unidirectional)	0.25° (4.362500 mrad)
Repeatability	< 0.1° (< 1.745 mrad)
Maximum Speed	18000°/s (3000 rpm)
Minimum Speed	0.017172°/s (299.703 μrad/s)
Speed Resolution	0.017172°/s (299.703 μrad/s)
Encoder Resolution	400 CPR (1600 states/rev)
Encoder Type	Rotary quadrature encoder
Communication Interface	RS-232
Communication Protocol	Zaber ASCII (Default), Zaber Binary
Data Cable Connection	Locking 4-pin M8
Maximum Torque	180 N-cm (254.9 oz-in)
Maximum Brake Torque	150 N-cm (212.4 oz-in)
Power Supply	24-48 VDC
Power Plug	2-pin Screw Terminal
Maximum Current Draw	3500 mA
Motor Steps Per Rev	200
Motor Type	Stepper (2 phase)
Motor Rated Current	3000 mA/phase
Default Resolution	1/64 of a step
Motor Frame Size	NEMA 23
LED Indicators	Yes
Mounting Interface	4.5 mm thru holes
Operating Temperature Range	0 to 50 °C
CE Compliant	Yes
Vacuum Compatible	No
Weight	1.926 kg (4.246 lb)

# X-NMS-E Series Charts

## Torque Speed Performance



## Torque Speed Performance



## Contact

Email: [contact@zaber.com](mailto:contact@zaber.com)

Phone (toll free Canada/USA): 1-888-276-8033

Phone (direct): 1-604-569-3780

Fax: 1-604-648-8033

Zaber Technologies Inc.

#2 - 605 West Kent Ave. N.

Vancouver, British Columbia

Canada, V6P 6T7

<https://www.zaber.com>